

Presenting the Cobalt CB12 Floorline Bed

COBALT
HEALTH

Style & Function

The Cobalt CB12 Floorline Bed is a stylish and fully functional Floorline Bed. It is an ideal floor level bed solution for use with falls risk patients and can be used in most environments, including the home and aged care facilities.

Clinical application:

Functions include electric height adjustment, back rest, knee bend, Trendelenburg and chair position, supported by a robust fabricated steel frame.

The bed has a height range between 15cm - 68cm, providing enhanced patient safety, whilst still allowing access for excellent care to be provided.



Colour	Code Single	Code King Single
Ash Brown	B24-S-AB	B24-KS-AB
Sublime Teak	B24-S-ST	B24-KS-ST
Tasmanian Oak	B24-S-TO	B24-KS-TO

PRODUCT FEATURES

Total safe working load (SWL) of the bed 250kg.

75mm twin Tente castors (four braking castors and four free-wheeling).

Electrically adjusted height range. The bed works within a height range of 15cm low height to a maximum height of 68cm.

Trendelenburg head and foot down tilt 14°.

Four section electronically operated mattress platform with independent adjustment of backrest angle (maximum 65°) and knee section angle (maximum 35°).

Four soft contoured mattress retainer handles.

Integral foot end mattress base extension. Extends the bed by 19.5cm.

Optional 3/4 length fold down side rails.

Removable timber head and foot panels.

One button chair positioning.

Under bed lighting.

Backlit handset.

Attendant control panel on foot board.

**HELPING
CARE
HAPPEN**

TECHNICAL INFORMATION

Basic dimensions

Overall length (not extended)	211cm
Overall length (when extended)	230.5cm
Overall width	S=92mm /KS =109cm
Overall width (rails fitted)	S=100mm /KS =120cm
Mattress platform length (between head and foot boards)	199.5cm
Mattress platform height range	15cm to 68cm
Back rest angle adjustment	0° to 65°
Knee bend angle adjustment	0° to 35°
Trendelenberg tilt adjustment (head and foot down)	0° to 14°

Electric parameter

Power input	100-240V AC 50/60Hz, max current 2.5A
Rate load	Interruption 10% max 2 minutes / 18 minutes
Leakage protection	Class 1 Type B
Waterproof grade	IP54



Mattress size

Recommended mattress size	Width: S=up to 88cm / KS =up to 107cm
	Length: S=up to 198cm / KS =up to 198cm
Maximum mattress depth (when side rails in use)	15cm
Minimum mattress depth (when side rails in use)	12.5cm

Bed weight

Without side rails	S = 119kg /KS = 125kg (approx)
With side rails	S = 138kg /KS = 144kg (approx)

Standard

CB12 beds are designed and manufactured in compliance with international Standard IEC 60601-2-52, where applicable.
ARTG Number - 522619

Safe Working Load

250kg

OPTIONAL EXTRAS

¾ Length fold down side rails

Self Help Pole

IV Pole

Grab Rail/Bar

Head, foot and side board colour options

COBALT

HEALTH

FOR FURTHER INFORMATION OR DEMONSTRATIONS, PLEASE CONTACT US

Victoria

vicsales@cobalthhealth.com.au

(03) 8521 8444

43 Paramount Bvd, Cranbourne West VIC 3977

New South Wales

sales@cobalthhealth.com.au

(02) 8853 1100

34/9 Salisbury Rd, Castle Hill NSW 2154

1800 417 822

cobalthhealth.com.au